

1

Model degeneracy

What it is

What it looks like

What it represents

How to avoid it

What it is

Technical Definition:

When a model places almost all probability on a small number of uninteresting graphs

- Most common "uninteresting" graphs:
 - Complete (all links exist)
 - Empty
- Model degeneracy is a sign of misspecification

The model you specified would almost never produce the network you observed

What it looks like in ergm

Your estimation will fail and you'll get an error like this


Error: Number of edges in a simulated network exceeds that in the observed by a factor of more than 20. This is a strong indicator of model degeneracy or a very poor starting parameter configuration. If you are reasonably certain that neither of these is the case, increase the MCMLE.density.guard control.ergm() parameter.

- What does this error message mean?
- When trying to fit this model, the algorithm heads off into networks that are much more dense than the observed network.
- Let's see why that is

SISMID: NME 2025


3

Let's take a simple example



- This network seems to have lots of triangles
 - 50 nodes
 - 4% density
 - 40% clustering
 - Fraction of all 2stars with the triangle completed
- So it would be natural to fit
 - edges + triangle model

Our network statistics




We can represent our model statistics as a 2D plot

And our observed graph in this plane

• Statistical theory guarantees that at the MLEs for θ :

E(netstats) = Observed

At the MLE, this is what the model produces



- The theory is not wrong
- Indeed, the means of the netstats are correct
- But this model produces a bimodal distribution to get those means
- It would never produce the observed graph

MCMC Dx for a model like this




Figure 5: MCMC diagnostic plots for the model with $\theta = (-3.43, 0.683)$.

- This is an example from fitting an edges+kstar(2) model
- If we let the MCMC iterate for a long time
- You can see the bimodal distribution in both the traceplots and the statistic densities

7

from Handcock 2003

What this represents: a bad model

 The MCMC-MLE theory is fine, and there's nothing wrong with the algorithm

The problem is the model
The simple edges + triangle (or edges + kstar(2)) model
would not produce our observed graph

 This is what model misspecification looks like with dependent data

Another way of thinking about this

- With a simple 2-parameter model, we can look at the networks produced (simulated) at all pairs of values of the coefficients
 - Ok, maybe not all, but many, many pairs
- Then answer the following questions:
 - How often does this model produce degenerate graphs?
 - How often does this model produce interesting graphs?

We already know it doesn't produce our network, but does it ever produce ANY networks that look reasonable?

And the answer is ... almost never




Figure 3: Cumulative Degeneracy Probabilities for graphs with 7 actors.

- This is the parameter space for an edges+kstar(2) model
- Shading indicates the frequency of reasonable networks
 - Black = none, all are degenerate
 - Gray = some
 - Light = more
- The only part of the parameter space with a high likelihood of a reasonable graph is close to the parameter set (0,0)
 - i.e., when there is no interesting structure to investigate

Graph from Handcock 2003

This is why we say this is a bad model

 These simple models with the homogeneous Markov graph statistics (k-stars and/or triangles) almost never produce interesting graphs

- So in general, it's best to avoid using these terms
- And instead use better specifications

Key references for model degeneracy

Handcock MS. (2003) Assessing Degeneracy in Statistical Models of Social Networks. CSSS working paper 39.

https://csss.uw.edu/node/4718

Schweinberger, M. (2011). Instability, Sensitivity, and Degeneracy of Discrete Exponential Families. *Journal of the American Statistical Association*, 106(496), 1361–1370.

https://doi.org/10.1198/jasa.2011.tm10747

SISMID: NME 2025

12